



SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

1. IDENTIFICATION

Product identifier

Product name KLEENSPRAY 65

Other means of identification

Product Code(s) 083817

Number 7Q0
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Lubricant. Industrial applications .

Uses advised against Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA, Inc.
1201 Louisiana St. Suite 1800
Houston, TX 77002
Phone: 713-483-5000

Contact Point Technical/ HSEQ

E-mail Address ProductSafety@total.com***

Emergency telephone number

Company Phone Number +1 (908) 862-9300
Emergency telephone +1 866 928 0789 (24h/24, 7d/7)
+1 215 207 0061 (24h/24, 7d/7)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)***

Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)***

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

Hazards not otherwise classified (HNOC)

None known

Other information**Physical-Chemical Properties**

Contaminated surfaces will be extremely slippery.***

Environmental properties

The product may form an oil film on the water surface that may stop the oxygen exchange. Should not be released into the environment.***

3. COMPOSITION/INFORMATION ON INGREDIENTS**Mixture**

Chemical Name	CAS-No	Weight %
Distillates (Petroleum), hydrotreated heavy Naphthenic***	64742-52-5	20-<30
Distillates (petroleum), hydrotreated light naphthenic***	64742-53-6	1-<3

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

* The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES**First aid measures for different exposure routes****General advice**

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.***

Eye contact

Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.***

Skin contact

Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. Take victim immediately to hospital.***

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately if symptoms occur.***

Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

Most important symptoms/effects, acute and delayed

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

Skin contact	Not classified based on available data.***
Eye contact	Not classified based on available data.***
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.***
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.***
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u>	Carbon dioxide (CO ₂). ABC powder. Use: Dry chemical. Alcohol-resistant foam. Water spray or fog.***
<u>Unsuitable Extinguishing Media</u>	Do not use a solid water stream as it may scatter and spread fire.***
<u>Special Hazard</u>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Thermal decomposition can lead to release of irritating gases and vapors; Sulfur oxides. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Flash back possible over considerable distance.***
<u>Explosion Data</u>	
<u>Sensitivity to Mechanical Impact</u>	None.
<u>Sensitivity to Static Discharge</u>	None.
<u>Protective Equipment and Precautions for Firefighters</u>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

General Information	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery.***
Other information	See Section 12 for additional information.
<u>Environmental precautions</u>	
General Information	Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Local authorities should be advised if significant

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

spillages cannot be contained. Try to prevent the material from entering drains or water courses. See Section 12 for additional Ecological Information.***

Methods and material for containment and cleaning up

Methods for cleaning up

Sweep up and shovel into suitable containers for disposal. Avoid dust formation. Powdered material may form explosive dust-air mixtures. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.***

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.***

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas. Avoid prolonged and repeated contact with the skin, especially with used or waste product. Do not wash off with: Fuel. Solvent. Abrasive. Avoid extended and repeated contact with the skin as this may cause skin conditions, which may also be aggravated by minor injuries or by contact with soiled clothing.***

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Protect from moisture. Keep in a banded area. Keep in properly labeled containers.***

Materials to Avoid

Strong oxidizing agents.***

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

Exposure controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.***

Individual protection measures, such as personal protective equipment

General Information

Protective engineering solutions should be implemented and in use before personal protective equipment is considered.***

Eye/face protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots.

Hand Protection

Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas. Avoid prolonged and repeated contact with the skin, especially with used or waste product. Do not wash off with: Fuel. Solvent. Abrasive. Avoid extended and repeated contact with the skin as this may cause skin conditions, which may also be aggravated by minor injuries or by contact with soiled clothing.***

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Color

black

Physical State @20°C

solid

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

Odor		Characteristic	
Odor Threshold		No information available	
Property	Values	Remarks	Method
pH		Not applicable	
Melting point/range		No information available	
Boiling point/boiling range		No information available	
Flash point	> 160 °C > 320 °F		Cleveland Open Cup (COC) ASTM D 92 Cleveland Open Cup (COC). ASTM D 92.
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
upper	-	No information available	
Lower	-	No information available	
Vapor Pressure	< 0.13 hPa	@ 38 °C	
Vapor density	> 5	(Air = 1)	
Relative density	< 1	@ 25 °C	
Density	< 1 g/cm3	@ 25 °C	
Water solubility		Insoluble	
Solubility in other solvents		Soluble in many common organic solvents	
logPow		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic		Not applicable	
Explosive properties	Not explosive		
Oxidizing Properties	No information available		
Possibility of hazardous reactions	See section 10		
Other information			
Freezing Point		No information available	
Note	• Please refer to Technical Data Sheet for further information		

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.***
Possibility of hazardous reactions	Hazardous polymerization does not occur. None under normal processing.***
Conditions to avoid	Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Take precautionary measures against static discharges. Strong oxidizing agents.***
Incompatible materials	Strong oxidizing agents.***

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Sulfur oxides, Hydrogen sulphide.***

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Principle Routes of Exposure	Inhalation, Ingestion, Eye contact, Skin contact.
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Skin contact	Not classified based on available data.***
Eye contact	Not classified based on available data.***
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.***
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.***

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Acute toxicity - Product Information**

Product Information	Product does not present an acute toxicity hazard based on known or supplied information.
Oral	Not classified based on available data***
Dermal	Not classified based on available data***
Inhalation	Not classified based on available data***

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (Petroleum), hydrotreated heavy Naphthenic*** 64742-52-5	LD50 > 5000 mg/kg (Rat - OECD401)	LD50 > 2000 mg/kg (Rabbit - OECD402)	LC50(4h) > 5.53 mg/l (Rat - aerosol - OECD403)
Distillates (petroleum), hydrotreated light naphthenic*** 64742-53-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	

Skin corrosion/irritation	Not classified based on available data.***
Serious eye damage/eye irritation	Not classified based on available data.***
Sensitization	Not classified as a sensitizer.
Carcinogenicity	This product is not classified carcinogenic.

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

IARC: (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans***

OSHA: (Occupational Safety & Health Administration) X - Present***

Mutagenicity

This product is not classified as mutagenic.

Reproductive toxicity

This product does not present any known or suspected reproductive hazards.

Target Organ Effects (STOT)

None known.***

STOT - single exposure

Not classified based on available data.***

STOT - repeated exposure

Not classified based on available data.***

Other adverse effects

Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

Aspiration hazard

Not classified.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Acute aquatic toxicity - Product Information**

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (Petroleum), hydrotreated heavy Naphthenic*** 64742-52-5		LL50(96h) > 100 mg/l (Pimephales promelas - static - OECD203)	EL50(48h) > 10000 mg/l (Daphnia magna - static - OECD202)	
Distillates (petroleum), hydrotreated light naphthenic*** 64742-53-6		LC50 (96h) > 5000 mg/L Oncorhynchus mykiss ()	EC50 (48h) > 1000 mg/L Daphnia magna	

Chronic aquatic toxicity - Product Information

No information available

Chronic aquatic toxicity - Component Information

No information available

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (Petroleum), hydrotreated heavy Naphthenic*** 64742-52-5	NOEL(72h) >= 100 mg/l (Pseudokirchnerella subcapitata - static - OECD201)	NOEL(21d) 10 mg/l (Daphnia magna - semi static - OECD211)		

Effects on terrestrial organisms No information available.***

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

Persistence and degradability**General Information** No information available.**Bioaccumulative potential****Product Information** No information available.**logPow** No information available**Component Information** No information available.**Mobility****Soil** Given its physical and chemical characteristics, the product has no soil mobility.**Air** Loss by evaporation is limited**Water** The product is insoluble and floats on water**Other adverse effects****General Information** No information available*****13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods** Dispose of in accordance with local regulations.*****Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.**California Hazardous Waste Codes** 221*****14. TRANSPORT INFORMATION****DOT** Not regulated**TDG** Not regulated**MEX** Not regulated**ICAO/IATA** Not regulated

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

IMDG/IMO Not regulated**ADR/RID** Not regulated**ADN** Not regulated**15. REGULATORY INFORMATION**

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
U.S.A. (TSCA)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.***

Chemical Name	Weight %	California Prop. 65
2-phenylpropene - 98-83-9	0.0024	Carcinogen***

Version GNAM



SDS # : 083817

KLEENSPRAY 65

Date of the previous version: 2016-05-12

Revision Date: 2018-10-04

Version 4

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Asphalt 8052-42-4	X***	X***	X***	X***
Graphite 7782-42-5	X***	X***	X***	

16. OTHER INFORMATION

NFPA	Health Hazard 1	Flammability 1***	Instability 0	Special hazards -
HMIS	Health Hazard 1	Flammability 1***	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2018-10-04
Revision Note *** Indicates updated section

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Legend

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDLH - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

Version GNAM



SDS # : 083817**KLEENSPRAY 65****Date of the previous version:** 2016-05-12**Revision Date:** 2018-10-04**Version** 4

S* - Skin notation
TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet

Version GNAM