

SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS #: 083823 MOLAC D

Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

1. IDENTIFICATION

Product identifier

Product name MOLAC D

Other means of identification

Product Code(s) 083823

Number4H4Substance/mixtureMixture

Recommended use of the chemical and restrictions on use

Identified uses Lubricant. Industrial applications .

Uses advised againstDo not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA, Inc.

1201 Louisiana St. Suite 1800

Houston, TX 77002 Phone: 713-483-5000

Contact Point Technical/ HSEQ

E-mail Address ProductSafety@total.com***

Emergency telephone number

Company Phone Number +1 (908) 862-9300

Emergency telephone +1 866 928 0789 (24h/24, 7d/7) +1 215 207 0061 (24h/24, 7d/7)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)***

Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)***



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

Hazards not otherwise classified (HNOC)

None known

Other information

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.***

Environmental propertiesThe product may form an oil film on the water surface that may stop the oxygen exchange.

Should not be released into the environment.***

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical Name	CAS-No	Weight %
Distillates (petroleum), hydrotreated heavy	64742-52-5	46-56
naphthenic		
Distillates (petroleum), hydrotreated light	64742-53-6	1-5
naphthenic		
Sulfur	7704-34-9	1-2

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.***

Eye contact Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while

rinsing.***

Skin contact Remove contaminated clothing and shoes. Wash skin with soap and water. Wash

contaminated clothing before reuse.

High pressure jets may cause skin damage. Take victim immediately to hospital.***

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. Get medical attention immediately if symptoms occur.***

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse

mouth. Call a physician or Poison Control Center immediately.***

Most important symptoms/effects, acute and delayed

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

Skin contactNot classified based on available data. High pressure injection of the products under the

skin may have very serious consequences even though no symptom or injury may be

apparent.***

Eye contact Not classified based on available data.***

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.***

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.***

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Foam. Carbon dioxide (CO2). ABC powder. Water spray or fog.***

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.***

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Thermal decomposition can lead to release of irritating gases and vapors; Sulfur oxides.***

Explosion Data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge

None. None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery.***

Other information See Section 12 for additional information.

Environmental precautions

General Information Do not flush into surface water or sanitary sewer system. Do not allow material to

contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained. Try to prevent the material from entering drains or water



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

courses. See Section 12 for additional Ecological Information.***

Methods and material for containment and cleaning up

Methods for cleaning up Sweep up and shovel into suitable containers for disposal. Avoid dust formation. Powdered

material may form explosive dust-air mixtures. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Keep in suitable, closed containers for disposal.***

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in

well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes

and clothing.***

Prevention of fire and explosion Take precautionary measures against static discharges. Ground/bond containers, tanks

and transfer/receiving equipment.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas. Do not wash off with:. Fuel. Solvent. Abrasive. Avoid extended and repeated contact with the skin as this may cause skin

conditions, which may also be aggravated by minor injuries or by contact with soiled clothing. Avoid prolonged and repeated contact with the skin, especially with used or waste

product.***

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture. Keep in properly

labeled containers.***

Materials to Avoid Strong oxidizing agents.***

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits Mineral oil mist:



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH

(TLV) TWA 5 mg/m³ (highly refined)

Exposure controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. When working in

confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for

breathing and wear the recommended equipment.***

Individual protection measures, such as personal protective equipment

General Information If the product is used in mixtures, it is recommended that you contact the appropriate

protective equipment suppliers. These recommendations apply to the product as supplied.

Eye/face protection If splashes are likely to occur, wear:. Safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing. Protective shoes or boots.

Hand Protection Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which

the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protection None required under normal usage. If exposure limits are exceeded or irritation is

experienced, NIOSH/MSHA approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local

regulations.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

not use abrasives, solvents or fuels. Do not dry hands with rags that have been

contaminated with product. Do not put product contaminated rags into workwear pockets. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas. Do not wash off with: Fuel. Solvent. Abrasive. Avoid extended and repeated contact with the skin as this may cause skin conditions, which may also be aggravated by minor injuries or by contact with soiled clothing. Avoid prolonged and repeated contact with the skin, especially with used or waste

product.***

9. PHYSICAL AND CHEMICAL PROPERTIES



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

Physical and chemical properties

Appearance paste
Color black
Physical State @20°C solid

Odor Characteristic

Odor Threshold No information available

Property Values Remarks Method

H Not applicable

Melting point/range No information available

Boiling point/boiling range Not applicable

Flash point >= 160 °C Cleveland Open Cup (COC)

ASTM D 92

>= 320 °F Cleveland Open Cup (COC).

ASTM D 92. aporation rate < 1 (n-Butyl acetate=1) @ 25 °C

Evaporation rate < 1 (n-Butyl acetate=1) @ 25 °C **Flammability Limits in Air** No information available

•

upper-No information availableLower-No information available

 Vapor Pressure
 < 0.15 hPa</td>
 @ 38 °C

 Vapor density
 > 8
 (Air = 1)

 Relative density
 0.96
 @ 25 °C

 Density
 0.96 g/cm3
 @ 25 °C

Water solubility 0.96 g/cm3 @ 25 °C Insoluble

Solubility in other solvents Soluble in many common

organic solvents

logPowNo information availableAutoignition temperatureNo information availableDecomposition temperatureNo information available

Viscosity, kinematic Not applicable

Explosive properties Not explosive

Oxidizing Properties No information available

Possibility of hazardous reactions See section 10

Other information

Freezing Point No information available

Note • Please refer to Technical Data Sheet for further information

10. STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under recommended storage conditions.***

Possibility of hazardous reactions Hazardous polymerization does not occur. None under normal processing.***



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

Conditions to avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Take

precautionary measures against static discharges.***

Incompatible materials Strong oxidizing agents.***

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Sulfur

oxides, Hydrogen sulphide.***

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Principle Routes of Exposure Inhalation, Ingestion, Eye contact, Skin contact.

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Skin contact Not classified based on available data. High pressure injection of the products under the

skin may have very serious consequences even though no symptom or injury may be

apparent.***

Eye contact Not classified based on available data.***

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.***

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.***

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity - Product Information

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Oral Not classified based on available data***

Dermal Not classified based on available data***

Inhalation Not classified based on available data***

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	LC50 (4h) 5.53 mg/l (Rat - Aerosol - OECD 403)
Distillates (petroleum), hydrotreated light naphthenic	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

64742-53-6			
Sulfur	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5.43 mg/L (Rat) 4 h
7704-34-9			

Skin corrosion/irritation

Serious eye damage/eye irritation

No.

Not classified based on available data.***
Not classified as a sensitizer.

Sensitization Carcinogenicity

This product is not classified carcinogenic.

Not classified based on available data.***

Chemical Name	ACGIH	IARC	NTP	OSHA
Distillates (petroleum),	-	-		-
hydrotreated heavy				
naphthenic				
64742-52-5				

Mutagenicity Not classified based on available data.***

Germ Cell Mutagenicity
Reproductive toxicity

Not classified based on available data.***
Not classified based on available data.***

Target Organ Effects (STOT) None known.***

STOT - single exposure
STOT - repeated exposure
Not classified based on available data.***
Not classified based on available data.***

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

Aspiration hazard Not classified based on available data.**

12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute aquatic toxicity - Product Information

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5		LC50 (96h) > 100 mg/l (Pimephales promelas - static - OECD 203)	EL50 (48h) > 10000 mg/l (Daphnia magna - static - OECD 202)	
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6		LC50 (96h) > 5000 mg/L Oncorhynchus mykiss ()	EC50 (48h) > 1000 mg/L Daphnia magna	
Sulfur 7704-34-9		-		

Chronic aquatic toxicity - Product Information

No experimental data available



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and	Toxicity to fish	Toxicity to
		other aquatic invertebrates		microorganisms
Distillates (petroleum),		NOEL (21d) 10 mg/l		
hydrotreated heavy		(Daphnia magna - semi		
naphthenic		static - OECD 211)		
64742-52-5		·		

Effects on terrestrial organisms No experimental data available .

Persistence and degradability

General Information No information available.

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information No information available.

Mobility

Soil Given its physical and chemical characteristics, the product has no soil mobility.

Air Loss by evaporation is limited

Water The product is insoluble and floats on water

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Should not be released into the environment. Dispose of in accordance with local

regulations.***

Contaminated packaging Dispose of in accordance with local regulations.

California Hazardous Waste Codes 221***



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

No information available

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Graphite	X***	X***	X***	
7782-42-5				
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	X***			
Sulfur 7704-34-9	X***	X***	X***	

16. OTHER INFORMATION

NFPAHealth Hazard 1Flammability 1***Instability 0Special hazards -HMISHealth Hazard 1Flammability 1***Physical Hazard 0Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2018-10-17

Revision Note *** Indicates updated section

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material



Date of the previous version: 2015-10-13 Revision Date: 2018-10-17 Version 1.02

Legend

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDHL - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet